



# Technical Data Sheet

PN# 20012107818

## Shieldex® Conductive Yarn

### Silver Plated Nylon 6, 78/18 dtex tri-lobe Z turns

- Purpose: Resistance heating RF Shielding, ESD and anti-microbial applications
- Description: 99% pure Silver plated Nylon 6 yarn 88/18f dtex tri-lobe
- Liner Resistance: < 200  $\Omega$ /cm
- Yield: 106,000 M/Kg
- Tenacity: Average 39 cN/tex
- Elongation: abt. 39%
- Denier: 70/18f (200-250 Z)
- Melt Point (F): 492



#### Package Properties

Core Type: 3 Deg-30 Min Cone 9"


Core Material: Pressed Paper or plastic

Product ID Color: Gray

Package Weight: 0.1 LB Nominal

Package Weight Control: +/- .1 lb. within single case

Cross section views of nylon fiber showing silver deposits



#### Accreditations:

RoHS: Compliant

Reach: Compliant

Acc. ISO 9001:2000



*A Woman's Owned Small Business*

**VTT/Shieldex Trading USA**  
**4502 Rt-31 Palmyra, NY, 14522**

**Phone: 315-597-1674**

**Fax: 315-597-6687**

**Email: [whog@rochester.rr.com](mailto:whog@rochester.rr.com)**

**[www.shieldextrading.net](http://www.shieldextrading.net)**

Statex Productions & Vertriebs GmbH  
Kleiner Ort 11 28357 Bremen Germany  
Tel: +49 421 275047/8, Fax: +49 421 273643  
[info@statex.de](mailto:info@statex.de)

  
© 2010 VTT  
Rev 1.20.10