




Technical Data Sheet

PN# 1100501130

SHIELDEX® BALTIMORE

- Purpose: RF shielding and microwave reflection
- Description: High conductive silver plated nylon knit mesh
- Surface Resistance: 0.8-1.2 ohms/□
- Shielding Effectiveness: 60db @ 30Mhz to 1Ghz average
- Abrasion Resistance: 10,0000 cycles
- Temperature Range: -30c to +90c
- Total Thickness: 0.18mm average
- Weight: 29-31g/Msq.
- Hole Count per 1 inch: (20 +/- 3)x(47 +/- 5)
- Roll Lengths: 100 LY average
- Roll Width: 52"
- Denier: 15
- Filament count: 1



Accreditations:
RoHS: Compliant
Reach: Compliant
Acc. ISO 9001:2000



A Woman's Owned Small Business

VTT/Shieldex Trading USA
4502 Rt-31 Palmyra, NY, 14522

Phone: 315-597-1674
Fax: 315-597-6687
Email: whoge@rochester.rr.com
www.shieldextrading.net

Statex Productions & Vertriebs GmbH
Kleiner Ort 11 28357 Bremen Germany
Tel: +49 421 275047/8, Fax: +49 421 273643
info@statex.de


© 2009 VTT
Rev 2.20.09