



Technical Data Sheet

PN# 1200131127

PRODUCT DATA

Purpose	Conductive fabric for gasket skin
Description	Conductive coated Silver plated Nylon fabric
Coating Surface	Yes (PUR)
Surface Resistivity	< 0.5 Ohms/□
Shielding Effectiveness	Average > 60 db from 300Mhz to 3Ghz
Temperature Range	-30 °C to 90 °C
Total Thickness	0.100mm ± 10%
Roll Width	127cm ± 2cm
Roll Length	Average 200m
Weight	50g/m² ± 10%
RoHS:	Compliant
Reach:	Compliant

PRODUCT APPLICATION

Outside skin for EMI/RFI fabric over Foam gaskets
Shielding material for laminated flat I/O Shielding Panels
EMI/RFI cable shielding



V Technical Textiles Inc./Shieldex-US
4502 SR-31, Palmyra, NY., 14522, USA
Tel: +1 315 597 1674, Fax: +1 315 597 6687
www.shieldextrading.net
whoge@rochester.rr.com

Alterations reserved
15.12.2010/05

Statex Produktions & Vertriebs GmbH
Kleiner Ort 11, 28357 Bremen, Germany
Tel: +49 421 275047/8, Fax: +49 421 273643
info@statex.de, www.statex.de