




Technical Data Sheet

PN# 1100601152PU

Conductive Metallized Nylon Fabric (Curtain+PU)

- Purpose: Conductive fabric for general use
- Description: 1 metalized layers Silver plated Nylon knit mesh fabric . Extreme high flexibility and transparency. With polyurethane protective coating
- Surface Resistance: 1..2 to 0.8 Ohms/□
- Shielding Effectiveness: Average 35 db from 30Mhz to 10Ghz
- Abrasion Resistance: 500,000 Cycles
- Temperature Range: -30°C to 90°C
- Total Thickness: 0.23mm nominal
- Number of Splices: 1/100M nominal
- Roll Widths: 110cm nominal
- Master Roll Lengths: 100M nominal
- Weight: 30-35g/sq.M



Accreditations:
RoHS: Compliant
Reach: Compliant
Acc. ISO 9001:2000

PRODUCT APPLICATIONS



A Woman's Owned Small Business

VTT/Shieldex Trading USA
4502 Rt-31 Palmyra, NY, 14522

Phone: 315-597-1674
Fax: 315-597-6687
Email: whoge@rochester.rr.com
Www.shieldextrading.net

Statex Productions & Vertriebs GmbH
Kleiner Ort 11 28357 Bremen Germany
Tel: +49 421 275047/8, Fax: +49 421 273643
info@statex.de


© 2010 VTT
Rev 6.20.10