



PN# 1200131127K



Shieldex® Berlin

- Purpose: Conductive fabric for general use,
- Description: Silver (Ag) plated fabric with conductive protective C2 (Black) coating on one side. Extreme high flexibility, advanced durability and reduced stress cracking.
- Raw material: Nylon ripstop fabric
- Surface Resistivity: Average < 0.3 Ohms / □ (max < 0.5 Ohms / □)
- RF Shielding Effectiveness: Average 60 db from 30Mhz to 10Ghz
- Abrasion Resistance: 1,000,000 Cycles
- Temperature Range: -40°C to 100°C / -40°F to 212°F
- Total Thickness: 0.004" (0.10mm) ± 12%
- Number of Splices: 1/100 Lm nominal
- Weight: 51 g/m² ± 10%
- Roll Widths: 52" (132cm) +1"
- Master Roll Lengths: Average 200 Lm / 280 Lyd



PRODUCT APPLICATION EXAMPLES

- ⇒ RF Enclosures
- ⇒ Base material for EMI/RFI gaskets
- ⇒ Base material for EMI/RFI garments
- ⇒ Shielding material for laminated flat I/O shielding panels
- ⇒ EMI/RFI cable shielding
- ⇒ Sensors

Accreditations:
RoHS: Compliant
Reach: Compliant
Acc. ISO 9001:2000

V Technical Textiles, Inc
 4502 State Rt. 31
 Palmyra, NY 14522
 Phone: 315-597-1674
 Fax: 315-597-6687
 Web: www.vtechtextiles.com
 Email: whoge@rochester.twcbc.com



Technical Textiles Inc.

A Woman's Owned Small Business

NWBOC®
 WBE CERTIFIED

NWBOC®
 EDWOSB CERTIFIED

Statex Productions & Vertriebs GmbH
 Kleiner Ort 11 28357
 Bremen Germany
 Tel: +49 421 275047/8,
 Fax: +49 421 273643
 info@statex.de